



Large Scale Visualization with ParaView

ATPESC 2018


Dan Lipsa
Kitware, Inc.

Outline




- Kitware
- Introduction
- Basic Usage
- Visualizing Large Models

Kitware





- Computer Vision
- Data and Analytics
- HPC and Visualization
- Medical Computing
- Software Process



Kitware – Computer Vision





Kitware – Data and Analytics






Kitware – HPC and Visualization

  ParaView  CMB  tomviz




Kitware – Medical Computing



Kitware – Software Process

- cmake, ctest, cdash



To Follow Along...


- Install ParaView 5.5.2
 - <http://www.paraview.org> → Download

Introduction


What is ParaView?

- An open-source, scalable, multi-platform visualization application.
- Support for distributed computation models to process large data sets.
- An open, flexible, and intuitive user interface.
- An extensible, modular architecture based on open standards.
- A flexible BSD 3 Clause license
- Commercial maintenance and support.

ParaView on the Desktop



ParaView on the Web




ParaView Scripting - Python



Python scripts can control ParaView with or without the GUI in order to create reproducible and customizable visualizations.


ParaView Immersive



ParaView for HPC




ParaView Catalyst



Community Atmosphere Model (CAM5) 2D (PS) 3D data (T), Spectral Element dynamic module.

ParaView Custom Application VeloView



Visualization of 3D LIDAR data.

Current ParaView Usage



- Used by academic, government, and commercial institutions worldwide.
- Downloaded ~135K times per year.
- HPCwire Editors' Choice 2010/2016 and HPCwire Readers' Choice 2010/2012/2015 Awards for Best Visualization Product or Technology.



Data Ranges

- Used for all ranges of data size.
- Landmarks of usage:
 - 6 billion structured cells (2005).
 - 250 million unstructured cells (2005).
 - Billions of AMR cells (2008).
 - Scaling test over 1 Trillion cells (2010).
 - 6.33 billion unstructured cells in Catalyst (2016).


ParaView Application Architecture



ParaView Development

- Started in 2000 as collaborative effort between Los Alamos National Laboratories and Kitware Inc. Sandia has been a major contributor since 2005.
 - ParaView 0.6 released October 2002.
- Paraview 3.0 release in May 2007.
 - GUI rewritten to be more user friendly and powerful.
- ParaView 4.0 released in June 2013.
 - Properties panel redesign for smoother interaction.
- ParaView 5.0 released in January 2016.
 - Updated to OpenGL 3.2 features. Huge performance improvements.

Current Funding



EXASCALE COMPUTING PROJECT

This research was supported by the Exascale Computing Project (17-SC-20-SC), a collaborative effort of the U.S. Department of Energy Office of Science and the National Nuclear Security Administration.

- ARL
- ERDC
- US Army (SBIR)
- US Air Force (STTR)
- ONR
- Support Contracts
 - Electricity de France
 - Microsoft



- Other contributors
 - Swiss National Supercomputing Centre
 - DOE SLAC
 - Ohio State
 - Mississippi State
 - RPI

Basics of Visualization


```

0265640 132304 133732 032051 037334 024721 015013 052226 001662
0265660 025537 064663 054606 043244 074076 124153 135216 126614
0265700 144210 056426 044700 042650 165230 137037 003655 006254
0265720 134453 124327 176005 027034 107614 170774 073702 067274
0265740 072451 007735 147620 061064 157435 113057 155356 114603
0265760 107204 102316 171451 046040 120223 001774 030477 046673
0266000 171317 116055 155117 134444 167210 041405 147127 050505
0266020 004137 046472 124015 134360 173550 053517 044635 021135
0266040 070176 047705 113754 175477 105532 076515 177366 056333
0266060 041023 074017 127113 003214 037026 037640 066171 123424
0266100 067701 037406 140000 165341 072410 100032 125455 056646
0266120 006716 071402 055672 132571 105645 170073 050376 072117
0266140 024451 007424 114200 077733 024434 012546 172404 102345
0266160 040223 050170 055164 164634 047154 126525 112514 032315
0266200 016041 176055 042766 025015 176314 017234 110060 014515
0266220 117156 030746 154234 125001 151144 163706 136237 164376
0266240 137055 062276 161755 115466 005322 132567 073216 002655
0266260 171466 126161 117155 065763 016177 014460 112765 055527
0266300 003767 175367 104754 036436 172172 150750 043643 145410
0266320 072074 000007 040627 070652 173011 002151 125132 140214
0266340 060115 014356 015164 067027 120206 070242 033065 131334
0266360 170601 170106 040437 127277 124446 136631 041462 116321
0266400 020243 005602 004146 121574 124651 006634 071331 102070
0266420 157504 160307 166330 074251 024520 114433 167273 030635
0266440 133614 106171 144160 010652 007365 026416 160716 100413
0266460 026630 007210 000630 121224 076033 140764 000737 003276
0266500 114060 042647 104475 110537 066716 104754 075447 112254
0266520 030374 144251 077734 015157 002513 173526 035531 150003
0266540 146207 015135 024446 130101 072457 040764 165513 156412
0266560 166410 067251 156160 106406 136770 030516 064740 022032
0266600 142166 123707 175121 071170 076357 037233 031136 015232
0266620 075074 016744 044055 102230 110063 033350 052765 172463


```




Data Types




Uniform Rectilinear
(`vtkImageData`)




Non-Uniform Rectilinear
(`vtkRectilinearData`)



Curvilinear
(`vtkStructuredData`)



Polygonal
(`vtkPolyData`)



Unstructured Grid
(`vtkUnstructuredGrid`)

Multi-block


Hierarchical Adaptive
Mesh Refinement
(AMR)

Hierarchical Uniform
AMR


Octree

More Information

- Help Menu
- *The ParaView Guide*
 - <http://www.paraview.org/paraview-guide/>
- Tutorials
 - <http://www.paraview.org/tutorials/>
- The ParaView web page
 - www.paraview.org
- ParaView discussion forum
 - <https://discourse.paraview.org/>



Help Menu



Basic Usage

User Interface


Menu Bar

Toolbars


Pipeline Browser

Properties Panel

Advanced Toggle



Getting Back GUI Components




Creating a Cylinder Source

1. Go to the Sources menu and select Cylinder.
2. Click the Apply button to accept the default parameters.





Simple Camera Manipulation

- Drag left, middle, right buttons for rotate, pan, zoom.
 - Also use Shift, Ctrl, Alt modifiers.
 - Also try holding down x, y, or z.



Creating a Cylinder Source

1. Go to the Source menu and select Cylinder.
2. Click the Apply button to accept the default parameters. 
3. Increase the Resolution parameter.




4. Click the  button again.


Pipeline Object Controls




Copy/Paste/Reset/Save Parameters




Display Properties




Change Render Properties

1. Scroll down to the Display group.
2. Click the  Edit button. (This button is replicated in the toolbar.)
3. Select a new color for the cylinder.


Render View Options



Change Render Properties

1. Scroll down to the Display group.
2. Click the  Edit button. (This button is replicated in the toolbar.)
3. Select a new color for the cylinder.
4. Scroll down to the View group.
5. Turn on the Axis Grid.

Advanced Properties



The screenshot shows the 'Properties' window in ParaView. At the top, there are buttons for 'Apply', 'Reset', 'Delete', and a help icon. Below these is a search bar with the text 'Search ... (use Esc to clear text)' and a gear icon to its right. The search bar is annotated with a red arrow and the text 'Search Properties'. The gear icon is annotated with a red arrow and the text 'Toggle Advanced Properties'. Below the search bar, there is a 'Display (GeometryRe)' button and two other buttons. The 'Representation' dropdown is set to 'Surface'. The 'Coloring' section has a 'Solid Color' dropdown and a color selection field. Below this are 'Show', 'Edit', and 'Rescale' buttons. The 'Styling' section has an 'Opacity' slider and a text input field with the value '1'. The 'Lighting' section is partially visible at the bottom.

Search Properties

Toggle Advanced Properties

Searching Properties

1. Type “specular” in the properties search box
2. Change Specular value to 1 (makes the cylinder shiny)



Searching Properties

1. Type “specular” in the properties search box
2. Change Specular value to 1 (makes the cylinder shiny)

Other interesting properties:


- Axes Grid
- Opacity
- Lights

Using Auto Apply

1. Click Auto Apply. 
2. Change the Resolution parameter again. 
3. Note that the visualization automatically updates without having to hit Apply.

Changing the Color Palette

1. Make sure the orientation axes are visible in the lower left corner. 




2. Click the color palette button  and change the colors.



3. Try several color palettes.

Color Palettes

 → Edit Current Palette...



Undo Redo



Undo



Redo




Camera
Undo



Camera
Redo

Creating a Cylinder Source

1. Go to the Source menu and select Cylinder.
2. Click the Apply button to accept the default parameters. 
3. Increase the Resolution parameter.




4. Click the  button again.
5. Delete the Cylinder. 

Supported Data Types

- ParaView Data (.pvd)
- VTK (.vtp, .vtu, .vti, .vts, .vtr)
- VTK Legacy (.vtk)
- VTK Multi Block (.vtm, .vtmb, .vtmg, .vthd, .vthb)
- Partitioned VTK (.pvtu, .pvti, .pvts, .pvtr)
- ADAPT (.nc, .cdf, .elev, .ncd)
- ANALYZE (.img, .hdr)
- ANSYS (.inp)
- AVS UCD (.inp)
- BOV (.bov)
- BYU (.g)
- CAM NetCDF (.nc, .ncdf)
- CCSM MTSD (.nc, .cdf, .elev, .ncd)
- CCSM STSD (.nc, .cdf, .elev, .ncd)
- CEAUcd (.ucd, .inp)
- CGNS (.cgns)
- CMAT (.cmat)
- CML (.cml)
- CTRL (.ctrl)
- Chombo (.hdf5, .h5)
- Claw (.claw)
- Comma Separated Values (.csv)
- Cosmology Files (.cosmo, .gadget2)
- Curve2D (.curve, .ultra, .ult, .u)
- DDCMD (.ddcmd)
- Digital Elevation Map (.dem)
- Dyna3D(.dyn)
- EnSight (.case, .sos)
- Enzo boundary and hierarchy
- ExodusII (.g, .e, .exe, .ex2, .ex2v., etc)
- ExtrudedVol (.exvol)
- FVCOM (MTMD, MTSD, Particle, STSD)
- Facet Polygonal Data
- Flash multiblock files
- Fluent Case Files (.cas)
- GGCM (.3df, .mer)
- GTC (.h5)
- GULP (.trg)
- Gadget (.gadget)
- Gaussian Cube File (.cube)
- JPEG Image (.jpg, .jpeg)
- LAMPPS Dump (.dump)
- LAMPPS Structure Files
- LODI (.nc, .cdf, .elev, .ncd)
- LODI Particle (.nc, .cdf, .elev, .ncd)
- LS-DYNA (.k, .lsdyna, .d3plot, d3plot)
- M3DCI (.h5)
- MFIX Unstructured Grid (.RES)
- MM5 (.mm5)
- MPAS NetCDF (.nc, .ncdf)
- Meta Image (.mhd, .mha)
- Miranda (.mir, .raw)
- Multilevel 3d Plasma (.m3d, .h5)
- NASTRAN (.nas, .f06)
- Nek5000 Files
- Nrrd Raw Image (.nrrd, .nhrd)
- OpenFOAM Files (.foam)
- PATRAN (.neu)
- PFLOTRAN (.h5)
- PLOT2D (.p2d)
- PLOT3D (.xyz, .q, .x, .vp3d)
- PLY Polygonal File Format
- PNG Image Files
- POP Ocean Files
- ParaDIS Files
- Phasta Files (.pht)
- Pixie Files (.h5)
- ProSTAR (.cel, .vrt)
- Protein Data Bank (.pdb, .ent, .pdb)
- Raw Image Files
- Raw NRRD image files (.nrrd)
- SAMRAI (.samrai)
- SAR (.SAR, .sar)
- SAS (.sasgeom, .sas, .sasdata)
- SESAME Tables
- SLAC netCDF mesh and mode data
- SLAC netCDF particle data
- Silo (.silo, .pdb)
- Spherical (.spherical, .sv)
- SpyPlot CTH
- SpyPlot (.case)
- SpyPlot History (.hscth)
- Stereo Lithography (.stl)
- TFT Files
- TIFF Image Files
- Tsurf Files
- Tecplot ASCII (.tec, .tp)
- Tecplot Binary (.plt)
- Tetrad (.hdf5, .h5)
- UNIC (.h5)
- VASP CHGCA (.CHG)
- VASP OUT (.OUT)
- VASP POSTCAR (.POS)
- VPIC (.vpc)
- VRML (.wrl)
- Velodyne (.vld, .rst)
- VizSchema (.h5, .vsh5)
- Wavefront Polygonal Data (.obj)
- WindBlade (.wind)
- XDMF and hdf5 (.xmf, .xdmf)
- XMol Molecule

Custom Data Import: Prototype with Python

- A “programmable source” lets you program data readers right in the GUI.
- Uses wrappings for the basic VTK classes.
- Good for prototyping readers.



Output Data Set Type: vtkPolyData

Script:

```
import random

output = self.GetOutput()
numpoints = 12

points = vtk.vtkPoints()
for p in xrange(numpoints):
    points.InsertNextPoint(random.random())
output.SetPoints(points)

verts = vtk.vtkCellArray()
for c in xrange(numpoints):
    verts.InsertNextCell(1)
    verts.InsertCellPoint(c)
output.SetVerts(verts)
```

<https://www.vtk.org/doc/nightly/html/>

Custom Data Import: Plugin Containing a Reader


- Plugins: shared object libraries that can be dynamically loaded into ParaView.
- C++ code and XML description of the interface.
- Any VTK reader object can be added.

Custom Data Import: Python Reader/Filter Plugin

- Only available in releases greater than 5.5.2 or in the **nightly** binaries.
- Python code and python decorators description of the interface (similar with the XML description).
- [PythonAlgorithmExamples.py](#)


Load disk_out_ref.ex2

1. Open the file `disk_out_ref.ex2` from the Examples directory.








Load disk_out_ref.ex2

1. Open the file disk_out_ref.ex2 from the Examples directory.
2. Load all data variables.



3. Click 

Data Representation



Common Filters



Calculator



Contour



Clip



Slice



Threshold



Extract Subset



Glyph



Stream Tracer



Warp (vector)




Group Datasets




Extract Level

Filters Menu




~ 150 filters

Quick Launch




- Used for searching for filters by name
- Keyboard shortcut
 - Ctrl-space for Windows & Linux
 - Alt-space for Mac

Apply a Filter

1. Make sure that `disk_out_ref.ex2` is selected in the pipeline browser.
2. Select the contour filter. 

Apply a Filter

3. Change parameters to create an isosurface at Temp = 400K.



Change to Temp →

Change to 400 →

Properties

Apply Reset Delete ?

Search...

Properties (Contour1)

Contour

Contour By: AsH3

Compute Normals

Compute Gradients

Compute Scalars

Isosurfaces

Value Range: [0.0804768, 0.184839]

0.132658146

Delete



Delete All

New Value


New Range

Scientific





Apply a Filter

1. Make sure that `disk_out_ref.ex2` is selected in the pipeline browser.
2. Select the contour filter. 
3. Change parameters to create an isosurface at $\text{Temp} = 400\text{K}$.
4. 



Create a Cutaway Surface

1. Select `disk_out_ref.ex2` in the pipeline browser.
2. From the quick launch, select Extract Surface.
3. A blue rectangular button with rounded corners. On the left side, there is a small icon of a shield with a green checkmark. To the right of the icon, the word "Apply" is written in a black, sans-serif font.



Create a Cutaway Surface

1. Select `disk_out_ref.ex2` in the pipeline browser.
2. From the quick launch, select Extract Surface.
3.  Apply
4. Create a clip filter. 
5. Uncheck Show Plane.  Show Plane
6.  Apply



Pipeline Browser Structure



Pipeline Browser Structure




Pipeline Browser Structure




Reset ParaView





Edit → Reset Session





Multiview





Multiview

1. Open disk_out_ref.ex2. Load all variables. 
2. Add Clip filter. 
3. Uncheck Show Plane. 
4. 
5. Color surface by Pres.




Multiview

6. Split the view horizontally. 
7. Make Clip1 visible. 
8. Color surface by Temp.



Multiview

6. Split the view horizontally. 
7. Make Clip1 visible. 
8. Color surface by Temp.
9. Right-click view, Link Camera...
10. Click other view.



Multiview

6. Split the view horizontally. 
7. Make Clip1 visible. 
8. Color surface by Temp.
9. Right-click view, Link Camera...
10. Click other view.
11. Click  -x and zoom in a bit.

Modifying Views




Modifying Views






Reset ParaView






Edit → Reset Session






Streamlines

1. Open disk_out_ref.ex2. Load all variables. 
2. Add Stream Tracer. 
3. Change Seed Type to Point Source.
4. Uncheck Show Sphere. Show Sphere
5. 

Streamlines

1. Open disk_out_ref.ex2. Load all variables. 
2. Add Stream Tracer. 
3. Change Seed Type to Point Source.
4. Uncheck Show Sphere. 
5. 
6. From the quick launch, select Tube
7. 

Getting Fancy


8. Select StreamTracer1.
9. Add Glyph filter. 
10. Change Glyph Type to Cone.
11. Change Vectors to V.
12. Change Scale Mode to vector.
13. Click reset  next to Scale Factor.
14. 
15. Color by Temp.

Getting Answers

- Where is the air moving the fastest?
Near the disk or away from it? At the center of the disk or near its edges?
- Which way is the plate spinning?
- At the surface of the disk, is air moving toward the center or away from it?

Reset ParaView


Edit → Reset Session




Common Data Analysis Filters



Extract Selection



Plot Global Variables Over Time



Plot Over Line



Plot Selection Over Time



Probe Location

Plotting


1. Open disk_out_ref.ex2. Load all variables. 

2. Clip,  uncheck, Show Plane , 

3. Select disk_out_ref.ex2.

4. Add Plot Over Line filter. 






3D Widgets




Placing 3D Line Widget Endpoints

- Use the p key to place alternating points.
 - Ctrl+p places at nearest mesh point.
- Use the 1 or 2 key to place the start or end point.
 - Ctrl+1 or Ctrl+2 places at mesh point.
- Drag the endpoints.
 - Use x, y, or z key to constrain to axis.
- Use widgets in Properties panel
 - E.g. Use Z Axis button and then edit points to place from (0,0,0) to (0, 0, 10).

Plotting



1. Open disk_out_ref.ex2. Load all variables. 
2. Clip,  uncheck, Show Plane , 
3. Select disk_out_ref.ex2.
4. Add Plot Over Line filter. 
5. Once line is satisfactorily located, 

Interacting with Plots

- Left, middle, right buttons to pan, zoom.
- Mouse wheel to zoom.
- Reset view to plot ranges. 

Plots are Views



- Move them like Views.
- Save screenshots.






Adjusting Plots

1. In Display section of properties panel, turn off all variables except Temp and Pres.
2. Select Pres in the Display options.
3. Change Chart Axis to Bottom – Right.
4. Verify the relationship between temperature and pressure.

Histogram / Bar Chart


1. Select disk_out_ref.ex2.
2. Filters → Data Analysis → Histogram 
3. Change Input Array to Temp.
4. 

Histogram / Bar Chart




Reset ParaView




Edit → Reset Session



Volume Rendering

1. Open disk_out_ref.ex2. Load all variables. A blue rectangular button with rounded corners, containing a small icon of a document with a green checkmark and the word "Apply" in a sans-serif font.
2. Change variable viewed to Temp.
3. Change representation to Volume.
4. In the Are you Sure dialog box, click Yes.

Volume Rendering + Surface Geometry

1. Open disk_out_ref.ex2. Load all variables. 
2. Change variable viewed to Temp.
3. Change representation to Volume.
4. Add Stream Tracer.  
5. Optional: Add Tubes and Glyphs.

Transfer Function Editor



Color Map Editor

Search...

Interpret Values As Categories

Mapping Data

Data:

Use log scale when mapping data to colors

Enable opacity mapping for surfaces

Automatically rescale transfer functions to fit data



Color Mapping Parameters

Color Space

Nan Color


Save as default Update

Modify Transfer Function

1. Select disk_out_ref.ex2.
2. Click Edit Color Map .
3. Click Choose preset .
4. Select Black-Body Radiation.
Apply. Close.
5. Try adding and changing control points.


Reset ParaView

Edit → Reset Session




Loading Data with Time




1. Open the file can.ex2.
2. Select all variables.







Animation Toolbar




Animation Pitfall


1. Go to first time step. 
2. Color by EQPS variable.
3. Play  (or skip to last time step ).

Animation Pitfall

1. Go to first time step. 
2. Color by EQPS variable.
3. Play  (or skip to last time step ).
4. Fix with Rescale to Data Range. 

Data Range Workarounds

- Go to representative time and hit 
- In Settings change On File Open to Goto last timestep.



Data Range Workarounds

- Set a custom range.






Data Range Workarounds

- Rescale to range over all timesteps



Query-Based Selection

1. Open can.ex2. All variables. 
2. Go to last time step. 
3. Edit → Find Data. 
4. Top combo box: find Cells.
5. Next row: EQPS, is \geq , and 1.5.
6. Click Run Selection Query.

Query-Based Selection

ParaView 3.8.0

Time: 0.00429999 43

EQPS Surface

Pipeline Browser

- builtin:
 - can.ex2

Object Inspector

Properties Display

Apply Reset

Variables

- Object Ids
- Global Elements
- EQPS
- Global Node Ids
- DISPL
- VEL
- ACCL
- KE
- XMOM
- YMOM

Apply Displacements 1

Check Selected Blocks Uncheck Selected Blocks

Find Data

Find **Cell** from **can.ex2**

EQPS is >= 1.5

Block ID is

Run Selection Query












Query Results

	EQPS	ObjectId	GlobalElementId	PedigreeElement
0	1.97048	1	36	36
1	1.51309	1	37	37
2	2.13094	1	76	76


Selection Color Labels None Label Color

Extract Selection Plot Selection Over Time Close



Brush Selection

- 
Surface Cell Selection
(shortcut: s)
- 
Surface Point Selection
(shortcut: d)
- 
Through Cell Selection
(shortcut: f)
- 
Through Point Selection
(shortcut: g)
- 
Select Cells (polygon)
- 
Select Points (polygon)
- 
Block Selection
(shortcut: b)
- 
Interactively Select Cells
- 
Interactively Select Points
- 
Hover Point Query
- 
Hover Cell Query


Selections

1. Open Find Data. The icon for the Find Data tool, showing a small 3D object with a blue and red gradient, surrounded by a dashed grid, with a mouse cursor pointing at it.
2. Make various brush selections.
3. Observe results in the Find Data dialog box.
4. Play with the Invert Selection and Show Frustum options.

Adding Labels


1. Go to the last time step. 
2. Open Find Data. 
3. Create query Global ID is min. Click Run Selection Query.
4. In the Cell Labels chooser, select EQPS.

Adding Labels

1. Go to the last time step. ▶▶
2. Open Find Data. The icon for the Find Data tool, showing a small grid with a blue and green gradient and a mouse cursor pointing to it.
3. Create query Global ID is min. Click Run Selection Query.
4. In the Cell Labels chooser, select EQPS.
5. When you are done, turn off the EQPS labels.

Reset ParaView


Edit → Reset Session



Visualizing Large Models


Data Parallel Pipelines

- Duplicate pipelines run independently on different partitions of data.




Data Parallel Pipelines

- Many operations will work regardless.
 - Example: Clipping.




Data Parallel Pipelines

- Many operations will work regardless.
 - Example: Clipping.








Data Parallel Pipelines


- Many operations will work regardless.
 - Example: Clipping.



- Will discuss those that don't later

Parallel Rendering





ParaView's Running Modes


<p>Built-in aka Standalone aka Serial</p>		<p>all components within one process (client may be GUI or pvpython) <code>paraview pvpython</code></p>
<p>Combined Server</p>		<p>data processing and parallel rendering in MPI job of combined processes. control from TCP connected client. <code>mpiexec -n x pvserver & paraview # or pvpython #+Connect</code></p>
<p>Batch</p>		<p>server is an MPI job which directly runs a python script <code>mpiexec -n x pvbatch \ vis_script.py</code></p>

DS = data server

RS = render server


Fetch Server Configuration

- File > Connect > Fetch Servers



Connect Unix/Mac

Mac Os: Install Xquartz

A screenshot of a macOS dialog box titled "Connection Options for 'COOLEY@ANL'". The dialog contains several fields for configuring a connection. The following fields are circled in red: "Xterm executable" with the value "/opt/X11/bin/xterm", "Username" with the value "danlipsa", "Number of nodes to reserve" with the value "2", "Number of minutes to reserve" with the value "10", "Account" with the value "ATPESC2017", and "Queue" with the value "training". Other fields include "SSH executable" (ssh), "Remote machine" (cooley.alcf.anl.gov), "ParaView version" (v5.4.0), "Client port" (11111), "Server port" (42844), and "Job name" (paraview_server). There are "Cancel" and "OK" buttons at the bottom right.

Connection Options for "COOLEY@ANL"

Xterm executable ...

SSH executable ...

Remote machine

Username

ParaView version

Client port ▾

Server port ▾

Number of nodes to reserve ▾

Number of minutes to reserve ▾

Account


Queue

Job name

Cancel OK

Connect Windows

Windows: Install PuTTY

A screenshot of a dialog box titled "Connection Options for 'windows to COOLEY...". The dialog box contains several fields and controls. The "SSH executable" field is set to "6)\PuTTY\plink.exe" and is circled in red. The "Remote machine" field is set to "cooley.alcf.anl.gov". The "Username" field is set to "YOURUSERNAME" and is circled in red. The "ParaView version" field is set to "v5.4.0". The "Client port" field is set to "11111" with a dropdown arrow. The "Server port" field is set to "22395" with a dropdown arrow. The "Number of nodes to reserve" field is set to "2" with a dropdown arrow. The "Number of minutes to reserve" field is set to "20" with a dropdown arrow. The "Account" field is set to "YOURPROJECT" and is circled in red. The "Queue" field is set to "default" and is circled in red. The "Job name" field is set to "paraview_server". At the bottom of the dialog box are "Cancel" and "OK" buttons.

Connection Options for "windows to COOLEY..."

SSH executable

Remote machine

Username

ParaView version

Client port ▾

Server port ▾

Number of nodes to reserve ▾


Number of minutes to reserve ▾

Account

Queue





Job name

Memory Inspector




Advanced Data Parallel Pipelines

- Some operations will have problems.
 - Example: External Faces




Advanced Data Parallel Pipelines

- Ghost cells can solve most of these problems.




Advanced Data Parallel Pipelines

- Ghost cells can solve most of these problems.




Data Partitioning

- Partitions should be **load balanced** and **spatially coherent**. Why?




Data Partitioning

- Partitions should be **load balanced** and **spatially coherent**.



Data Partitioning


- Partitions should be load balanced and spatially coherent. A random partition with ghost cells will replicate the entire dataset on all nodes.




Load Balancing/Ghost Cells

- Automatic for Structured Meshes.
- Partitioning/ghost cells for unstructured is “manual.”
- Use Ghost Level Generator to create
- Legacy option: D3. Also repartitions

Extract Surface
without ghost
cells



Extract Surface
after D3



Thank you!

Questions?